Primero

LUXURY VINYL TILES





Content

TABLE

#01	Introducing Primero p. 5	#05	The perfect finish p. 12
#02	Why choose Primero?	#06	Looks p. 14
#03	Primero, a quality multi-layered floor	#07	Meet IVC Group p. 32
#04	Installation p. 10	#08	Technical specifications p. 34



Introducing

PRIMERO

Luxury Vinyl Tiles (LVT) floors are a popular choice in homes because of the numerous benefits they offer. The durable vinyl planks and tiles consist of different layers, each one offering a specific characteristic. Developed and made in Belgium, Primero comes with the well-known benefits of LVT flooring: comfort, softness and warmth, while providing a seven-layer floor that can withstand everyday family use.


Our design team went the extra distance to create an accessible collection: a wide range of natural wood and stone effects in appealing shades ensures that Primero can be enjoyed in every style of home.

66

Made in Belgium, this quality floor is comfortable, durable, and a delight to the eye.

99

DESIGN FLOORS Primero



Why choose Primero?

BENEFITS OF PRIMERO

Soft, warm and quiet, Primero is a floor that makes everyone feel comfortable. What's more, its long-lasting finish is beautifully simple to look after.

Affordable quality

Made in Belgium, Primero's Primero finds inspiration This means a floor that's ready for modern life.

Natural beauty

seven-layer construction is in the beauty of wood and strong, stable and resistant stone. Its minimal pattern to temperature changes. repeat means every room enjoys a natural look.

Easy-going comfort

Choosing Primero means choosing a floor that's quickly installed and easy to maintain. Its soft underfoot feel, warmth and noise absorption make sure you enjoy a comfortable home.

For a better planet

Because it lasts, Primero is a great sustainable choice. With recycled content and low impact manufacturing in Belgium, this is a floor that takes its responsibility to the planet seriously.









DESIGN FLOORS Primero

Primero, a quality multi-layered floor

HOW IS PRIMERO MADE?

Our R&D and production teams in Belgium are constantly innovating and always looking for ways to make better floors. Primero is a result of this collective effort: developed and manufactured in-house using the best technology available to us today. Primero showcases the innovation of IVC Group with a compact multi-layer construction that delivers everyday performance. Scratch-resistant, stainproof and with excellent dimensional stability, this is a floor that's made to stick around.

Let's look at Primero's multi-layer construction in a little more detail:



Protective Superguard® for resistance and easy maintenance



A protective PU lacquer gives Primero its scratch-resistance and an ability to fight off stains. Standing up to family life, pet-proof and easy to maintain, this protective layer enhances usability.

A reliable wear layer



The 0.3 mm thick wear layer makes sure that Primero's planks and tiles are tough enough for family homes. In fact, Primero achieves the highest class possible for residential use thanks to a wear layer that's made in-house for reliability and quality. That's why we back Primero with a long 12-year residential warranty.

A design layer for a unique natural look



With Primero we aim to create beautiful nature-inspired designs printed with eco-friendly inks. The process is completely in-house, from inspiration to creation and production, so Primero comes with exclusive designs that you can't find anywhere else. What's more, we use a large pattern and cut out planks and tiles cleverly to avoid obvious repeats. This gives Primero a more natural look.

Double glass-fibre layer for a stable floor





Primero's patented dual glass-fibre construction is the reason for its class-leading dimensional stability. It makes sure that Primero stays locked to the ground, regardless of temperature. Keeping movement to the bare minimum, the dual layers mean Primero can be used throughout the home. So, whether a steamy bathroom, summery garden room or an open plan living space with underfloor heating, Primero is up for the challenge.

A durable compact core





While you may never see it, the compact core is crucial to Primero's durability. It provides the floor's indentation resistance to furniture and high heels. No matter how many times you rearrange your room, Primero stays in great shape. Even better, we make this strong and durable compact core with up to 50% recycled content. Underlining just how important this layer is, Primero Click has a thicker compact core for a strong and secure click joint.

A sustainable backing layer with extra grip





Connecting Primero to the prepared subfloor beneath, the backing layer has an important part to play. We've added an embossed 'grip' texture to give the adhesive extra hold. There's also a direction arrow, so you know exactly which way to lay your plank and tile to create an authentic looking floor. This layer features up to 70% recycled content, another way we're reducing Primero's impact on the planet.

GLOSSARY







Green, eco-friendly, durable



Dimensional stability



Scratch & stain



Moisture protection


DESIGN FLOORS Primero

Installation

VINYL CLICK & DRYBACK SYSTEM

Primero is remarkably easy to install. Available in either glue or click flavours, you can choose the method that's best for you. Stick down or lock together, Primero's world-class dimensional stability and high-strength compact layer deliver a lasting result.

CLICK DRYBACK





For detailed Click installation instructions, please check



For detailed **Dryback** installation instructions, please check www.installandclean.com/en/lvtdryback





Choose the correct underlay/adhesive Click Dryback Small temperature Big temperature Self-adhesive Adhesive fluctuations fluctuations underlay Big temperature Acoustics Acoustics fluctuations and/or important very important high temperatures Flex Pro Acoustic Pressure High underlay Comfort underlay Sensitive **Temperature** underlay Adhesive Adhesive


The perfect finish

ACCESSORIES TO EASE YOUR MIND

For the perfect finish, you need the perfect range of accessories. From skirtings and profiles to cleaning and maintenance, we have everything you need, made to the same exacting standards as your Primero floor.



For more info, please check www.xtrafloor.com





1. Stair profiles



3. Expansion profile



5. Paintable skirting





2. End profile



4. Radiator cap



6. Underlay



8. Joint filler

Looks

CLOSER TO NATURE


Designed in Belgium from exacting studies of original materials, Primero captures the nuance and variety of nature, presenting a range of decors varying from light and subtle to dark and rustic. A detailed and sharp emboss and refined bevel make it even more realistic. Our design team went the extra distance to create an accessible collection: a wide range of natural wood looks in vivid colours and realistic stone looks in broadly appealing shades. Primero ensures there is a floor for every home.











14 DESIGN FLOORS Primero 1



Summer Oak





24210







24929













4 sided bevel



Thickness 2 mm



Thickness 4.5 mm

Wear layer 0,3 mm



Wear layer 0,3 mm

16 DESIGN FLOORS Primero


Sebastian Oak
















Colombia Pine





24115

A STATE OF THE STA

24966

Dryback
Available in:
16.3 x 98.8 cm

4 sided bevel

Click Unidrop®
Available in:
19.1 x 1316 cm

4 sided bevel

Thickness
2 mm

Click Unidrop®
Available in:
19.1 x 1316 cm

Thickness
4 sided bevel

Wear layer 0,3 mm <u>×</u>

Wear layer 0,3 mm

Chapel Oak




















Major Oak





1047



24241

24856

Dry BACK 16,3

Dryback Available in: 16.3 x 98.8 cm CLICK

Click Unidrop® Available in: 19.1 x 131.6 cm

4 sided bevel

__

4 sided bevel

Thickness 2 mm

Thickness 4.5 mm

×


Wear layer 0,3 mm

<u>×</u>

Wear layer 0,3 mm

Matera Stone







Dryback Available in:32.9 x 65.9 cm

Click Unidrop® Available in: 32,4x 65,5 cm



4 sided bevel



4 sided bevel




Thickness 2 mm



Thickness 4.5 mm




Wear layer 0,3 mm





Cosmic





CLICK

Click Unidrop® Available in: 324x 65,5 cm

<u>—</u>

46945

4 sided bevel

Dryback Available in:32.9 x 65.9 cm

__

4 sided bevel

Thickness 2 mm ______

Thickness 4.5 mm

<u>×</u>

Wear layer 0,3 mm



Wear layer 0,3 mm

Navona Stone





46126



46922





Dryback Available in:32.9 x 65.9 cm



Click Unidrop® Available in: 324x 65.5 cm









Meet IVC Group

IVC Group is a global player in the design and manufacturing of flooring solutions including Carpet Tiles, Luxury Vinyl Tiles (LVT), Heterogeneous Vinyl for use in business, public and private environments. Accountable for our actions, we design and make floors responsibly in Belgium, developing a circular approach to the future of flooring.

IVC Group is part of Mohawk Industries Inc., the world's largest flooring company. With 1,500 employees and 7 production sites in Europe and Russia, IVC Group produces over 130,000,000 m² of flooring every year.

Did you know..

that IVC Group employs over 30 different nationalities worldwide? That's the many cultures and inspirations which go into our eclectic floor designs, explaining their global appeal.







How we make our floors better for the environment?

At IVC Group, we truly believe in products that are developed with the future in mind. That's why we take the time to pause and reflect on the impacts of our entire strategy and operation, and we aim to contribute to the welfare of our planet and our people.





Read all about it in our sustainability whitepaper



Technical specifications

TECHNICAL INFO OF PRIMERO

		Dryback	Click	
PRODUCT INFORMATION				
Level of use	EN ISO 10874	23 - 31	23 - 31	
Total thickness	EN ISO 24346	2 mm	4.5 mm	
Wear layer	EN ISO 24340	0,3 mm	0,3 mm	
Wear Layer PUR treatment		Superguard®	Superguard®	
Total weight glm ²	EN ISO 23997	3328	7953	
SIZE & PACKING				
Planks	EN ISO 24342	16.3 x 98.8 cm	19.1 x 131.6 cm	
Tiles	EN ISO 24342	32.9 x 65.9 cm	32.4 x 65.5 cm	
Box planks		3.87 m ² 24 pcs/box	1.76 m ² 7 pcs/box	
Box tiles		3.90 m ² 18 pcs/box	1.49 m² 7 pcs/box	
TEST RESULTS				
Inflammability	EN 13501	Bfl-S1		
Abrasion group	EN ISO 660-2	Class T		
tch resistance EN 16094 MSR-A		. ≤MSR-B2		
Squareness	EN ISO 24342	≤ 0.20 mm		
Straightness	EN ISO 24342a	≤ 0.35 mm		
Dlip resistance EN 13893		[DS	
Slip restraint	aint DIN 51130 R10		10	
Residual indentation	EN ISO 24343-1	≤ 0,10 mm		
Furniture leg resistance	re leg resistance EN ISO 16581 No cracks, r		no damage	
Curling	EN ISO 23999	≤ 2 mm	≤ 1 mm	
Dimensional stability	EN ISO 20326	Norm: ≤ 1 0,25 1 % Average result: ≤ 0,10%	Norm: ≤ 1 0,15 1 % Average result: ≤ 0,10%	
Thermal resistance R	EN 12667	0.04 m ² K/W	0.04 m ² K/W	
Acoustic insulation	EN ISO 717-2	4 dB		
Acoustic insulation + Xtrafloor Acoustic Comfort		19 dB		
Castor chair resistance	EN ISO 4918	No damage to wearlayer, no delamination		
Stain resistance	EN ISO 26987	Very good		
Light fastness	EN ISO 105-B02	≥ 6		
Underfloor heating and cooling	EN 12524	Suitable, max 27°C		
Warranty (year)		12 Residential - 5 Commercial		















